GP-SR1-PC200

- Structural and electrical safety
- Ease of installation and maintenance
- Programmatic cell sorting for matched cells
- Active balancing technology
- Compatibility with leading inverters
- Scalability up to 215kWh



GP-SR1-PC200

15kWh Module

51.2V Low Voltage System

The Gobel Power Battery GP-SR1-PC200 is a lithium iron phosphate (LFP) battery pack for use with an external inverter. A single Battery Module has about 15kWh capacity and can reach to 215kWh if 15 modules parallel connected.

Accessories GP-SR1-PC200

| Parts | Quantity | Details | |
|------------------|----------|--|--|
| Battery Model | 1 | GP-SR1-PC200 | |
| Mounting Bracket | 2 | Fix the battery to the wall | |
| RS232 Cable | 1 | Communication cable between BMS and PC software | |
| Network Cable | 1 | Communication cable between BMS and Inverter | |
| DC Power Cable | 2 | Pair of 3AWG DC Power Cable connect with Inverter, 1m, M8 terminal | |



TECHNICAL PARAMETERS GP-SR1-PC200

| Battery Module | GP-SR1-PC200 | | | | | |
|-----------------------------|--|---------|---------|----------|--|--|
| Dimensions (H/W/D) | 882.5 X 482.6 X 241 mm | | | | | |
| Weight | 118 kg | | | | | |
| | | | | | | |
| Number of Modules | 1 | 2 | 3 | 15 | | |
| Usable Energy [1] | 14.3kWh | 28.6kWh | 42.9kWh | 214.5kWh | | |
| Nominal Capacity | 280Ah | 560Ah | 840Ah | 4200Ah | | |
| Max Cont. Output Current | 200A | 400A | 600A | 3000A | | |
| Max Cont. Output Power | 10.2kW | 20.4kW | 30.6kW | 153kW | | |
| Max Cont. Input Current [2] | 140A | 280A | 420A | 2100A | | |
| Max Cont. Input Power | 7.2kW | 14.4kW | 21.6kW | 108kW | | |
| | | | | | | |
| Nominal Voltage | 51.2 VDC | | | | | |
| Operating Voltage | 44 ~ 55.2 V | | | | | |
| Operating Temperature | -20 °C to +50 °C | | | | | |
| Battery Cell Technology | Lithium Iron Phosphate (cobalt-free) | | | | | |
| Communication | CAN / RS485 / RS232 | | | | | |
| Enclosure Protection Rating | IP21 | | | | | |
| Round-Trip Efficiency | ≥95% | | | | | |
| Scalability | Max. 15 Modules in Parallel (214.5 kWh) | | | | | |
| Certification | CE / UN38.3 | | | | | |
| Applications | ON Grid / ON Grid + Backup / OFF Grid | | | | | |
| Warranty [3] | 10 Years | | | | | |
| Compatible Inverters | Refer to Gobel Power Inverter Compatibility List | | | | | |

^[1] DC Usable Energy, Test conditions: 100% DOD, 0.2C charge & discharge at + 25 °C . System Usable Energy may vary with different inverter brands.



^[2] Charge derating will occur below +15 °C.

^[3] Conditions apply. Refer to Gobel Power Limited Warranty Letter.